

LII twin coil solar hot water cylinder specifications

- twin-coil, vented cylinders solar cylinders
- (unvented and custom cylinders also available to special order)
- grade 3
- UK manufactured
- Clearskies 'approved'
- manufacturer's warranty period: 2 years

Material Top & Body gauge: 0.7mm copper

Material Base gauge: 1.6mm copper

Boiler Coil: 28mm OD copper tube

Solar Coil: 16.5mm ID finned copper tube with a heating surface 1.62 square metres

Connections: 22mm compression on cylinder inlet and outlet and boiler coil, 15mm compression on solar coil. (Other connection sizes available to special order.)

Insulation Thickness: 50mm polyurethane foam.

Thermostat Pockets Available: 10mm (standard) 12mm & 15mm available to special order

Immersion heater boss (can be omitted to special order)

Cylinder Tested to: Vented 1.45 bar

Coils Tested to 7.0 bar

All cylinders are supplied with "Clearskies" labels attached (waterproof heavy duty laser labels).

Delivery usually 5-7 working days, delivered within the UK via Interlink Express. Single cylinders are packed into cardboard boxes with a 25mm polystyrene pad at the base of the box and cardboard/paper packing to the sides. If several cylinders are ordered, they will be supplied shrink wrapped on a pallet.

